


CONNECTOR BOX SERIES




ENE8207




ENE8211



ENE 8407



ENE8411



ENE8215



ENE8415

CONNECTION WITH OR WITHOUT FERRULES

SUPPLIED WITH INSULATED BACK PLATE AND TRANSPARENT PROTECTIVE FRONT COVER. SELF-EXTINGUISHING
960 MOUNTING METHODS

- FIX ON DIN-RAIL
- ON PLATE WITH 2 SCREWS

WHEN INSTALLING UNDER A FRONT PLATE, A BLANKING PLATE CAN BE CLIPPED ONTO THE FRONT PLATE

INSULATION PROTECTION ON EACH BAR

EACH BAR CAN BE LABELLED USING CAB 3™

CONFORM TO STANDARD EN60947-1

ICC: 20KA PEAK



Item No.	Bus Bar Spec.	No. Of Bus Bar	Conductors with starfix temules X-section (mm ²)	Cond. wout ferr. X-section (mm ²)	Dimensions (L × W × H) (mm)
ENE8207	5 × ϕ 5.5mm 2 × ϕ 7.5mm	2	1.5 to 6 6 to 16	2.5 to 6 10 to 25	65 × 42 × 50
ENE8211	7 × ϕ 5.5mm 2 × ϕ 7.5mm 2 × ϕ 9mm	2	1.5 to 6 6 to 16 10 to 16	2.5 to 6 10 to 25 10 to 35	100 × 42 × 50
ENE8215	11 × ϕ 5.5mm 2 × ϕ 7.5mm 2 × ϕ 9mm	2	1.5 to 6 6 to 16 10 to 16	2.5 to 6 10 to 25 10 to 35	135 × 42 × 50
ENE8404	4 × ϕ 6mm	4	1.5 to 6	2.5 to 6	43 × 85 × 50
ENE8407	5 × ϕ 5.5mm 2 × ϕ 7.5mm	4	1.5 to 6 6 to 16	2.5 to 6 10 to 25	65 × 85 × 50
ENE8411	7 × ϕ 5.5mm 2 × ϕ 7.5mm 2 × ϕ 9mm	4	1.5 to 6 6 to 16 10 to 16	2.5 to 6 10 to 25 10 to 35	100 × 85 × 50
ENE8415	11 × ϕ 5.5mm 2 × ϕ 7.5mm 2 × ϕ 9mm	4	1.5 to 6 6 to 16 10 to 16	2.5 to 6 10 to 25 10 to 35	135 × 85 × 50